



- PRO TLAKOVOU ZKOUSKU SVARU ZHOTOVIT DO JEDNOHO CELA (POZ. 02) ZAVIT. PO ZKOUSCE VODOTESNE ZASLEPIT. ZKUSEBNI TLAK 0.3 MPa.  
- FOR PRESSURE TEST OF WELD MAKE THREAD TO ONE CYLINDER END (POS. 02). AFTER TEST, WATER-RESISTANT BLIND. TESTING PRESSURE 0.3 MPa (3 bar)

SVĀŘENO

-	-	①	-	MATERIAL	DLE ROZPISKY
-	-	②	-	PRESNOST ISO 2768-mH	POLOTOVAR
-	-	③	-	TOLEROVANI ISO 8015	C. HMOTNOST [kg]
-	-	④	-		83.638
-	-	⑤	-		
-	-	⑥	-		
-	-	⑦	-		
-	-	⑧	-		
-	-	⑨	-		
ZMENA		DATUM	INDEX	PODPIS	
KRESLIL	L.Skalicky	DATUM	26.04.11	MERITKO	NAZEV
PREZKOUSEL	Podzemsky			1:2	VNITRNI VALEC DODAVATEL - TURECKO
TECHNOLOG	----			(1/1)	
C. SESTAVY	-			PROMITANI	
PODOBNOST	-				CISLO VYKRESU
PC DATA	M3624.03-11-10F001				M3624.03-11-10C001
					Listu I
					List I
					FORMAT A2