



NEKÓTOVANÉ HRANY SRAZIT NA 1x45°.
ZUŠLECHTĚNO NA 700 - 800 MPa.

Ra 3,2 (✓)

General tolerances / Obecné tolerance									Material: 1.1191 (12 050)		Projection
Lenght/Delka			Rad., Cham./Zaob., Zkos.			ISO 2768 m K			Angle/Uhel		
fr./od	to/do	toler.	fr./od	to/do	toler.	fr./od	to/do	toler.			
0.5	6	± 0.1	0.5	3	± 0.2	0	10	± 1°	Raw material: -		
6	30	± 0.2	3	6	± 0.5	10	50	± 0°30'	Polotovar:		
30	120	± 0.3	6	-	± 1	50	120	± 0°20'	Mass: 88,36 kg		
120	400	± 0.5				120	400	± 0°10'	Hmotnost:		
400	1000	± 0.8				400	-	± 0°5'	Partlist		
									Kusovník No		
									Rev.: 00		
									Date / Datum		
									Name / Jmeno		
									Page: 1 of: 1		
									Replacement for: Zamena za:		
									Scale: 1:5		
									Filename: Vnitřní spodní kroužek.idw		
									Sheet format: A3		
									Drawing Nr.: 1001005		
									Cislo vykresu:		
									Cust. Drawing Nr.:		
									Zakazn. cislo vykresu:		
Rev.	EC-Nr.		Date Datum	Name Jmeno	Approved Schvaleno						