


LEGEND OF ROOMS				
NUMBER	DESCRIPTION	AREA [m²]	FLOOR FINISHING	NOTES
-1.01	CORRIDOR	20.3	CONCRETE	-
-1.02	CORRIDOR	20.3	CONCRETE	-
-1.03	GARAGE	2255.7	EPOXY COAT	-
-1.04	TECH. ROOM	15,66	EPOXY COAT	-
-1.05	PARM ROOM	15.66	EPOXY COAT	-

LIST OF LINTELS					
No.	Pcs.	Description	Length (mm)	Reinforcement ϕ (mm)	Note
(L6)	1	LINTEL HELUZ, h=250mm	1750	8	—
(L7)	3	R.C. LINTEL, h=250mm	1400	NOT DETERMINED	—
(L8)	2	R.C. LINTEL, h=250mm	3100	NOT DETERMINED	—

LEGEND OF MATERIALS	
	REINFORCEMENT CONCRETE, C25/30
	STEEL, GALVANIZED COATING
	CERAMIC BRICKS HELUZ AKU, TH. 250mm

- NOTES:
- DIMENSION ARE IN mm
 - DIMENSION OF OPENINGS WILL BE MEASURED IN SITU
 - HYDRO-INSULATION AGAINST GROUND WATER IS PROVIDED BY WATERPROOF REINFORCEMENT CONCRETE C25/30, XC3, XD2, XF3, XA1
 - STEEL CONSTRUCTION IS DRAWN IN MODULAR DIMENSION AND CAN BY MODIFIED ACCORDING STATIC DESIGN OF CONSTRUCTION.
 - SURFACE OF MASONRY WALLS WILL PLASTER CEMIX INTERNAL TH. 10mm
- (N1) DRAINAGE OUTLET (FLOOR SLOPED IN 1‰)



0.000 = 324,95 m n.m. / COORDINATE SYSTEM S-JTSK			
DESIGNED BY	SUPERVISOR		VUT BRNO FACULTY OF CIVIL ENGINEERING VEVER 33116 602 00 Brno
Bc. DANIEL NIESNER	Doc. Ing. Jiří Sedláč		
MASTER'S THESIS BLOCK OF FLATS IN PASSIVE STANDARD		FORMAT	10 x A4
		DATE	01/2014
D.1.1-06 – LAYOUT OF 1ST UNDG. FLOOR		ST. SKUPINA	CA2NPS1
		MĚŘITKO	1:50