

TruBend Series 3000 since YOM 2015 Installation height 350 mm

TruBend 3066 3100	Height [mm] OW	EV70-M	WB120 - WB 350	RollBend 200 - 600	EV/S-W4-W5	EV W6-W80	KEY W8-W24	EV001-EV007 „R3„/S	EV Z4-10/90°	FEV W6-12	EV W80-120	EV/H W6-W50	EV001/H-EV007/H	VLMBN *	VLMDN
Height [mm] EV ▶		100	100	100	100	100	100	100	100	108	120	150	150	185	195
OW.../K	120														
OW210/S 280/K	140														
	160														
	180														
	200														
OW.../S	220														
OW210/S	240														

A > 40 mm

A 25-40 mm

impossible

A = Removal height

*Attention: only when using 5-axis backgauge

TruBend Series 3000 since YOM 2015 Installation height 500 mm

TruBend 3100 with extended Installation height 3170	Height [mm] OW	EV70-M	RollBend 200 - 1250	EV/S-W4-W5	EV W6-W80	KEY W8-W24	EV001-EV007 („R3„/S)	EV Z4-10/90°	FEV W6-12	EV W80 - 120	EV/H W6-W50	EV001/H - EV007/H	VLMBN *	VLMDN
Height [mm] EV ▶		100	100	100	100	100	100	100	108	120	150	150	185	195
OW.../K	120													
OW210/S 280/K	140													
	160													
	180													
	200													
OW.../S	220													
OW210/S	240													
	260													
	280													
OW300/S	300													
	320													
	340													
	360													

A > 60 mm

A 45-60 mm

nicht möglich

A = Removal height

* Attention: only when using 5-axis backgauge