



LIST OF WINDOWS							1
SIGN.	SCHEME	DESCRIPTION	DIMENSIONS	PCS			
			W/H [mm]	FF	SF	TOTAL	
W1		<p>FRAME</p> <p>spruce glue laminated wooden frame</p> <p>tilting and opening inside</p> <p>thickness 78 mm</p> <p>$U_w=0.90 \text{ W/m}^2\cdot\text{K}$</p> <p>Sunlight factor 62 %</p> <p>Sound dampening 35 dB</p> <p>FITTINGS</p> <p>all-round fitting</p> <p>safety points</p> <p>safety against faulty handling</p>	<p>GLAZING</p> <p>triple glazing</p> <p>filled with argon</p> <p>$U_g= 0.5 \text{ W/m}^2\cdot\text{K}$</p> <p>COLOUR</p> <p>black/brown RAL 8022</p> <p>PARAPET</p> <p>External: galvanized steel sheet</p> <p>thickness 1.6 mm</p> <p>expanded length 320 mm</p> <p>Internal: chipboard laminated oak with nose</p> <p>thickness 20 mm</p>	1500x1000	26	16	42
W2		<p>FRAME</p> <p>spruce glue laminated wooden frame</p> <p>tilting inside</p> <p>thickness 78 mm</p> <p>$U_w=0.90 \text{ W/m}^2\cdot\text{K}$</p> <p>Sunlight factor 62 %</p> <p>Sound dampening 35 dB</p> <p>FITTINGS</p> <p>all-round fitting</p> <p>safety points</p>	<p>GLAZING</p> <p>triple glazing</p> <p>filled with argon</p> <p>$U_g= 0.5 \text{ W/m}^2\cdot\text{K}$</p> <p>COLOUR</p> <p>black/brown RAL 8022</p> <p>PARAPET</p> <p>External: galvanized steel sheet</p> <p>thickness 1.6 mm</p> <p>expanded length 320 mm</p> <p>Internal: chipboard laminated oak with nose</p> <p>thickness 20 mm</p>	1000x500	2	2	4